


Infrared LED TriBrid Cameras



GOLDEN STATE INSTRUMENT CO.



Exmor R

GS-SLVR-409

GS-SLVR-410

Vandal Dome or Weatherproof Bullet
TriBrid Technology 1080P 1920 x 1080 HD-TVI/AHD
960H Composite 1280TVL Video
True Day/Night ICR 21/36 IR LED
Dual Voltage 12VDC/24VAC



GSI TriBrid cameras have HD 1080P color resolution using the latest HD-TVI(High Definition Transport Video Interface) AHD (Analog High Def) Technology. Using this technology, this gives an easy path to getting High Def video. Functions like a traditional analog camera using coax BNC or standard video baluns. Video transmission of over 1000ft on CCTV grade RG-59 coax. Real-time fluid video with no latency, unlike IP systems. It's TriBrid Technology allows connection to Legacy 960H systems too with its composite 1280TVL Output.

Features:

- 1/2.9" 1080P Sony 2.4MP HD Sensor
- IMX322 + FH8530C
- 1080P Full HD 1920x1080 TVI / AHD
- Legacy 960H Composite 1280TVL
- Versatile 3-Axis Camera Mount
- 2.8-12 Varifocal Megapixel Lens
- 21/36 Pieces of IR LEDs (Up to 50/70ft Illumination)
- Aesthetically Pleasing Housing for Indoor/Outdoor Use
- IP 66 Weather Rating
- Vandal Resistant Dome or Bullet
- True Day/Night ICR
- 2DNR (Digital Noise Reduction)
- 12VDC/24VAC Dual Voltage
- Solid and compact Aluminum construction

DUAL BNC Outputs:

Yellow BNC: 1080P HDTV
Black BNC: 1080P AHD or 960H CVBS
Default 960H Analog
Hold Joystick Right 5 Seconds for 1080P AHD
Hold Joystick Left 5 Seconds for 960H CVBS Analog

WARNING:

Observe Correct Voltage and Polarity,

Do Not Point Camera Directly into Sun,

Failure to Observe Warnings May Void Warranty.



**3002 Dow Ave Suite 228
Tustin, CA 92780 USA**

**Sales : 888-808-0909
Tech Support: 714-730-6889
Email : gsi@goldenstateinst.com**

www.goldenstateinst.com

Model	GS-SLVR-409	GS-SLVR-410
Signal System / Output	TriBrid HD-TVI/AHD/960H Composite BNC Output	
Image Sensor	1/2.9" 1080P Sony 2.4MP HD Sensor IMX322 + FH8530C	
Lens	2.8-12mm Varifocal Lens	
Pixel Count /Resolution	Full HD 1080P 1920(H) x 1080 (V)	
IR LEDS	21 Pieces (Up to 50ft)	36 Pcs (Up to 70ft)
Min. Illumination	0.1 LUX (IR OFF) 0 LUX (IR On)	
Light Compensation	DWDR (Digital Wide Dynamic Range)	
S/N Ratio	More than 52dB (AGC OFF)	
Shutter Speed	1/60 ~ 1/1000,000 sec.	
Voltage	12VDC / 24VAC Dual Voltage	
Power Consumption	500mA (Max)	
Dimensions	5.2" Diameter x 4.4" H	2.8" x 10.25"
Weight	1.4 lbs	1.8 lbs
Operating Temperature	-10°C to 50°C	