



**ULTRA**

**CLEAR COAT**

**2.1 VOC**

**2:1 MIX**

**HIGH GLOSS**

**GOOD LEVELING**

**EASY APPLICATION**



**FOR USE ONLY BY PROFESSIONALS.  
NOT FOR SALE TO OR USE BY GENERAL PUBLIC**

**Notice to purchaser - Limited Warranty.** The following is made in lieu of all express or implied rights, warranties and conditions. All goods are manufactured of first class materials.

Neither seller nor manufacturer has control over the use and application of the product.

It is the responsibility of the purchaser to determine the suitability of the product for its intended use.

The liability of the seller and manufacturer shall not exceed the purchaser price of the product.

**WARNING! FLAMMABLE LIQUID AND VAPOR.**  
VAPORS AND SPRAY MIST HARMFUL IF INHALED.  
MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS SUCH AS DIZZINESS, HEADACHE OR NAUSEA. MAY CAUSE NOSE, THROAT, EYE AND SKIN IRRITATION.  
(FOLLOW ALL DIRECTIONS AND CAUTIONS ON BACK PANEL)

**WARRANTY:** The recommendations for application of this product are based on data obtained by our own research facilities and is believed accurate. The manufacturer warrants all material sold by it against defects in the material but does not warrant its fitness for any specific application use. The manufacturer makes no other warranty of this material express or implied. This product is intended to be used solely by professionally trained personnel using proper equipment.

Made in EU  
5 LITERS

**Euro Refinish, Inc**  
816 Towne Center Dr,  
Pomona, CA 91767  
(888) 966-9433

**Description:** Euro Refinish Clear Coat have been formulated to provide easy mixing, ease of application, fast dry times and excellent buffability. The acrylic resins used in both Clear & Activator are extremely durable, therefore, they will retain the initial gloss and D.O.I. (mirror image) very well. There are three Activators designed for use with the Clear Coat. The specific Activator controls the dry time, reaction time, gloss and buffability. **BASECOATS:** Apply the basecoats per mixing and application directions of basecoat label. Allow sufficient flash times and the basecoat is completely dry before applying Euro Refinish Clear Coat.

**DIRECTIONS:**

1. Read all label directions, warnings and cautions on paint and catalyst.
2. Mixing Directions for Clear Coat with Activator:  
2 Parts Clear  
1 Part Activator
3. Adjust air pressure to 50-60 psi at the gun (siphon); 40-45 psi (gravity); 10 psi (HLVP).
4. Apply 2 full coats, allowing 10-15 minutes flash time between coats. Allow ample flash times.
5. When force drying, flash for 10-15 minutes, than force dry for 40 minutes at 140°F. Clear may be wet sanded after 2-4 hours. Baking the clear will increase gloss.
6. Accelerator: Add 2 to 4 oz. can be added to a gallon of catalyzed clear to improve drying times. Note that use of any Accelerator will shorten Pot Life and slightly reduce gloss. If an Accelerator is added to EURO REFINISH Clear, it MUST also be added to the color.
7. Wet sand with 1500 grit or finer paper after 8 hours. Buff with appropriate compound.
8. Clean spray equipment immediately after use with lacquer thinner.

**WARNING! FLAMMABLE, VAPOR AND SPRAY MIST HARMFUL. MAY CAUSE LUNG IRRITATION AND ALLERGIC RESPIRATION REACTION.** Keep away from heat, sparks and open flames. Isocyanates can cause lung and skin sensitization and lung damage. Not to be used by persons who have lung or breathing problems or have reaction to isocyanates. Based on animal data, prolonged and repeated overexposure may cause adverse liver and kidney effects at various sites. Do not inhale vapors. Do not get in eyes, on skin or on clothing. Do not take internally. Use only in well ventilated areas. Wear appropriate, properly fitted

NIOSH/MSHA approved respirator as directed by the manufacturer when airborne contaminate level(s) exceed exposure limits indicated in Section II of the MSDS. Select positive pressure supplied respirator (TC-19C or equivalent) for isocyanates. Protect hands with impervious rubber gloves. Gloves must be checked before each use for signs of degradation, penetration and for proper functioning. Wear eye and face protection.

Keep container closed when not in use. Since empty containers retain products residue and vapor, observe precautions even after container is empty. Subject to hazardous waste treatment storage and disposal requirements under RCRA. Incineration at EPA approved facility or dispose of in compliance with federal, state and local regulations. For further healthy and safety information and first aid, read the current Material Safety Data Sheet. Read warning on individual labels before opening each container.

**FIRST AID:** In case of headache, dizziness, respiratory irritation or other systems of overexposure, move from affected area and avoid further exposure. If symptoms persist, contact physician immediately.

In case of skin contact, wash skin thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately. In case of eye contact flush eyes with running water for at least 15 minutes and get medical attention immediately. If ingested, contact physician immediately.

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentration and inhaling this product may be harmful or fatal.

Proposition 65 Statement: **WARNING!** This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

**KEEP OUT OF THE REACH OF CHILDREN**

Contents: Xylene CAS# 1330-20-7, Acetone CAS# 67-64-1, Butyl Acetate CAS# 123-86-4,  
2-Methoxy-1-Methyl Ethyl Acetate CAS# 108-65-6, Ethyl Benzene CAS# 100-41-4,  
Methyl 1,2,2,6,6-Pentamethyl-4-Piperidyl Sebacate CAS#82919-37-7  
EMERGENCY TELEPHONE NUMBER: CHEMTREC U.S 1-800-424-9300  
Sprayable 2.1 VOC lbs/gal

\*\*\*\*\* **DANGER** \*\*\*\*\*

