

Saleh & Abdulaziz
Abahsain Co. Ltd.



JCB POWER PRODUCTS | GENERATORS AND LIGHTING TOWERS

ةيسمرش لاءةاضإلأ جاربأو تادلومرلأ | **JCB**



GENERATORS AND LIGHTING TOWERS.

JCB POWER PRODUCTS OFFER AN EXTENSIVE RANGE OF OVER 170 GENERATORS AND LIGHTING TOWERS. AS WITH ALL OUR MODELS, THESE MACHINES ARE DESIGNED TO MEET THE RIGOURS OF THE LOCAL ENVIRONMENT WHILST BEING EASY TO MAINTAIN AND OFFERING A HIGH LEVEL OF RELIABILITY.

ةقاطال دي لوت تاجت نم نم ةعساو ةعومج JCB رفوت
ةيسمرشال ةعاضل اءربو اءلوم 170 ىل ع دي زي امل
ءارفون يتل التال ديومر ل عي م لثم ؁ تانيك امل هذ ن
ةئيبلل ةقاشل عاضوال تابلطتم يبلتل اهمريمصت مرت
هتاذ تقوال يف اهت ناي ص لهسي امنيب ةيلحمل
ةيقوئومرل نم اقئاف ىوتسم رفوت امك ؛

Efficient performance.

Tried and proven performance, economy and low noise to suit a range of applications.

Total control.

Digital control panels provide easy machine monitoring, as well as enabling remote programming for hard to reach sites.

Easy servicing.

Our large service doors provide excellent access, for ultimate ease of maintenance.

Freedom of movement.

A central lift point and standard-fit fork pockets make these generators easily portable and simple to secure in transit.

لاءفلا ءاأالا

مرستي يداصتقا ؁ هءافك تبتثو هب قوئوم ءاأا
تاقاببطتل نم ةعساو ةقاب مئاليل ءاضووال ضافخاب

لمراش مركحت

امك ةنيك املرل ءلهس ةقابر ةيمقرل مركحتل تاجول رفوت
هيلل لوصولو بعصي يتل عاقومرل دعب نع ةجمربل نكمرت

ةمدخل ءلوهس

ريغ ءلوهسو اعئار ألوصولو ةريبك ال ةمدخل ذفانم رفوت امك
ةنايصلل ققوبسم

ةكرحل ةيرج

ةيسايقل ءكوشل تاجتفو ةيزكرمرل عفرل ةطقن ن
هنيماؤو آلهس اؤمرأ تادلومرل هذ ليمرحت لعجت ةمئالمرل
اشلس لقنل دن



G20QS-G220QS GENERATOR RANGE.

THE G20QS TO G220QS ARE THE VERY LATEST MODELS TO BE ADDED TO JCB'S DIESEL GENERATOR RANGE. AS WITH ALL OF OUR MODELS, THESE MACHINES ARE DESIGNED TO GENERATE POWER WITH GREAT PRODUCTIVITY AND EFFICIENCY AND FITTED IN THE SMALLEST CANOPY TO DELIVER A COMPACT AND LIGHTWEIGHT MODEL.

مرت JCB. نم لزي دل تادلوم ةومر جمل اهت فاضا مرت يتل قاطلإ
، انفرط نم ىرخآل تاليدوم ل عيمرچ لثم ، تانيكامل هذه مري مرصت
اهت يثبت مرت ةقوب سم ريغ ةيلاعفو ةقئاف ةيجاتنإ عم ةقاطل دي لوتل
ص. ألي دومر جنم تل ةلظم يف



NEW QS RANGE												
Model		G20QS	G27QS	G40QS	G45QS	G65QS	G90QS	G115QS	G140QS	G165QS	G200QS	G220QS
Type - Open / Canopy		Canopy	Canopy	Canopy	Canopy	Open / Canopy	Open / Canopy	Open / Canopy	Open / Canopy	Canopy	Canopy	Canopy
Engine make		JCB Diesel by Kohler	JCB Diesel by Kohler	JCB Diesel by Kohler	JCB Diesel by Kohler	4 Cylinder JCB DIESELMAX	4 Cylinder JCB DIESELMAX	4 Cylinder JCB DIESELMAX	4 Cylinder JCB DIESELMAX	6 Cylinder JCB DIESELMAX	6 Cylinder JCB DIESELMAX	6 Cylinder JCB DIESELMAX
Prime Power (PRP) at 50Hz 400/230V	kVA	19.3	25.5	36.8	41.7	63	81.3	105	126.3	152.5	180	200.2
Standby Power (ESP) at 50Hz 400/230V	kVA	21.1	28	40.4	45.7	71	89.6	116	140.3	168.8	198	220.2
Prime Power (PRP) at 60Hz 380V	kVA	-	-	-	-	63	89.3	106.6	128.6	154.2	180.4	200.9
Standby Power (ESP) at 60Hz 380V	kVA	-	-	-	-	69	98.8	117.8	142.8	169.5	198.4	220.9
Prime Power (PRP) at 60Hz 220/127V	kVA	-	-	-	-	71	89.3	106.6	128.6	155.7	182.2	202.8
Standby Power (ESP) at 60Hz 220/127V	kVA	-	-	-	-	78	98.8	117.8	142.7	171.1	200.3	223.1
Prime Power (PRP) at 60Hz 480/227V	kVA	-	-	-	-	75.5	89.3	106.6	126	156	182.5	203.3
Standby Power (ESP) at 60Hz 480/227V	kVA	-	-	-	-	83	98.8	117.8	140	171.6	200.7	223.5
Length	mm	1750	2250	2250	2250	2750	2850	2850	2850	3800	3800	3800
Width	mm	750	800	800	800	1830	1830	1830	1830	2050	2050	2050
Height	mm	1250	1250	1250	1250	1140	1140	1140	1140	1140	1140	1140




8 - 730KVA STANDARD RANGE.



STANDARD RANGE

Model		G8X - G45X	G8QX - G45QX	G65X - G140X	G65QX - G140QX	G144X - G220X	G144QX - G220QX	G275X - G600X	G275QX - G600QX	G306X - G726X	G306QX - G726QX
Type - Open / Canopy		Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy	Open	Canopy
Engine make		Yanmar	Yanmar	JCB	JCB	IVECO	Iveco	Scania	Scania	MTU	MTU
Prime Power (PRP) at 50Hz 400/230V	kVA	8.8 - 41.8	8.8 - 41.8	59.6 - 126.3	59.6 - 126.3	130 - 200	130 - 200	250 - 550	250 - 550	278.1 - 663.8	278.1 - 663.8
Standby Power (ESP) at 50Hz 400/230V	kVA	9.7 - 45.9	9.7 - 45.9	66.4 - 140.2	66.4 - 140.2	143 - 220	143 - 220	275 - 601	275 - 601	305.5 - 732.7	305.5 - 732.7
Prime Power (PRP) at 60Hz 380/220V	kVA	10.7 - 42.5	10.7 - 42.5	63 - 128.6	63 - 128.6	130 - 205	130 - 205	250 - 558.1	250 - 558.1	250 - 690	250 - 690
Standby Power (ESP) at 60Hz 380/220V	kVA	11.6 - 48	11.6 - 48	69 - 142.8	69 - 142.8	143 - 225	143 - 225	275 - 608.1	275 - 608.1	275 - 746	275 - 746
Prime Power (PRP) at 60Hz 220/127	kVA	10.7 - 50.7	10.7 - 50.7	71 - 128.6	71 - 128.6	145 - 228.2	145 - 228.2	295.9 - 556.9	295.9 - 556.9	300 - 697.4	300 - 697.4
Standby Power (ESP) at 60Hz 220/127	kVA	11.6 - 56.1	11.6 - 56.1	78 - 142.8	78 - 142.8	159 - 251.6	159 - 251.6	325.3 - 606.8	325.3 - 606.8	330 - 769.1	330 - 769.1
Prime Power (PRP) at 60Hz 480/277V	kVA	10.7 - 51	10.7 - 51	75.5 - 128.6	75.5 - 128.6	149.9 - 228.9	149.9 - 228.9	297.1 - 561.6	297.1 - 561.6	300 - 703.3	300 - 703.3
Standby Power (ESP) at 60Hz 480/277V	kVA	11.7 - 56.4	11.7 - 56.4	83 - 142.8	83 - 142.8	165.2 - 252.4	165.2 - 252.4	326.7 - 611.9	326.7 - 611.9	330 - 775.5	330 - 775.5
Length	mm	1450 - 1850	1475 - 2100	2150 - 2450	2750	2900	3300	3000 - 3600	3800 - 4500	3310 - 3600	4100 - 5000
Width	mm	620 - 780	750 - 975	780 - 795	1100	900	1200	1160 - 1460	1400 - 1800	1390 - 1604	1600 - 2100
Height	mm	620 - 1500	1104 - 1349	1492 - 1590	1760	1600 - 1634	1958	1759 - 2090	2290 - 2340	2061 - 2121	2200 - 2369
Weight inc. oil and water	Kg	279 - 626	456 - 944	1110 - 901	1590 - 1720	1412 - 1521	2301 - 2517	2172 - 3313	3436 - 5023	3096 - 4671	4531 - 6881

730 - 3300KVA HEAVY RANGE.



HEAVY RANGE

Model		G730QX/X - G2450QX/X	G950QX/X - G2500QX/X	G860QX/X - G3300QX/X	G975QX/X - G3850QX/X
Type - Open / Container		Open / Container	Open / Container	Open / Container	Open / Container
Engine make		Mitsubishi	Mitsubishi	MTU	MTU
Prime Power (PRP) at 50Hz 400/230V	kVA	670 - 2293	-	728 - 3026	-
Standby Power (ESP) at 50Hz 400/230V	kVA	738 - 2480	-	860 - 3330	-
Prime Power (PRP) at 60Hz 480/277V	kVA	-	864 - 2276	-	920 - 3531
Standby Power (ESP) at 60Hz 480/277V	kVA	-	967 - 2523	-	1011 - 3884
Length (Canopy)	mm	6058 - 12192	6058 - 12192	6058 - 12192	6058 - 12192
Width (Canopy)	mm	2438	2438	2438	2438
Height (Canopy)	mm	2896	2896	2896	2896

MOBILE AND STATIC LIGHTING TOWERS.



LIGHTING TOWERS

Model		LT9	LT9 LED	LTM9	LTC9	LTB9
Lights		4 x 1000W Metal Halide	6 x LED lamps	4 x 1000W Metal Halide	4 x 1000W Metal Halide	4 x 1000W Metal Halide
Engine		Yanmar	Yanmar	Yanmar	Yanmar	No engine
Prime power (PRP) at 50Hz 230V	kVA	6.4	6.4	5.1	6.4	No engine
Prime power (PRP) at 60Hz 380V	kVA	7.2	7.2	6.0	7.2	No engine
Length (deployed)	mm	2330	2330	2760	2648	1950
Width (deployed)	mm	2450	2450	2780	2617	2250
Height (deployed)	mm	9000	9000	9070	9000	9000
Noise level at 7m	dBA	62	62	71	62	0

VALUE ADDED.

JCB'S WORLDWIDE CUSTOMER SUPPORT IS FIRST CLASS. WHATEVER YOU NEED AND WHEREVER YOU ARE, WE'LL BE AVAILABLE QUICKLY AND EFFICIENTLY TO HELP MAKE SURE YOUR MACHINERY IS PERFORMING TO ITS FULL POTENTIAL.

ةعرس ىصقأب كيلى لصنس ،نوكت امرنيأو كتاجايتح نوكت
اهتقاط لماركب ةنيكامل اءادأ نم دكأتلل ةءافك ىلعأو





ONE COMPANY, OVER 300 MACHINES.

Saleh & Abdulaziz Abahsain Co. Ltd.

Heavy Equipment Division

AL-KHOBAR P.O. Box 209 Al - Khobar 31952 - Saudi Arabia

Head Office: Tel. 03-898-4045 Ext: 322, 310 Fax: 899-1557

Mobile: 055-7163980 Email: hedho@abahsain.net

KHOBAR BR. Tel. 03-857-2296 Fax: 03-858-8241

RIYADH BR. Tel. 01-495-1076 Fax: 01-495-4900

JEDDAH BR. Tel. 02-682-0944 Fax: 02-683-3124

YANBU BR. Tel. 04-322-4200 Fax: 04-322-7877

JUBAIL BR. Tel. 03-341-5845 Fax: 03-341-6113

ABHA BR. Tel. 07-227-0780 Fax: 07-227-1499



**Saleh & Abdulaziz
Abahsain Co. Ltd.**

©2009 JCB Sales. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, photocopying or otherwise, without prior permission from JCB Sales. All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependant upon the exact specification of machine. They should not therefore be relied upon in relation to suitability for a particular application. Guidance and advice should always be sought from your JCB Dealer. JCB reserves the right to change specifications without notice. Illustrations and specifications shown may include optional equipment and accessories. All images are correct at time of print. The JCB logo is a registered trademark of J C Bamford Excavators Ltd.