



Australis®

AUSTRALIS CeilingFlat IS A
PREMIUM INTERIOR ULTRA FLAT
CEILING PAINT FORMULATED TO
PRODUCE A SUPERIOR FINISH.

•12 YEAR•
GUARANTEED
NOT TO CRACK PEEL OR BLISTER*
*SEE CONDITIONS ELSEWHERE ON LABEL



Colourtrend Paints
(Aust) Pty Ltd
ABN 50 057 442 323
481 Victoria Street
Wetherill Park NSW 2164
Tel (02) 9756 2400
Fax (02) 9756 2405
815-04104



high opacity
CeilingFlat
ULTRA FLATTINTABLE



AUSTRALIS CeilingFlat IS A
PREMIUM INTERIOR ULTRA FLAT
CEILING PAINT FORMULATED TO
PRODUCE A SUPERIOR FINISH.

•12 YEAR•
GUARANTEED
NOT TO CRACK PEEL OR BLISTER*
*SEE CONDITIONS ELSEWHERE ON LABEL



Colourtrend Paints
(Aust) Pty Ltd
ABN 50 057 442 323
481 Victoria Street
Wetherill Park NSW 2164
Tel (02) 9756 2400
Fax (02) 9756 2405
815-04104



high opacity
CeilingFlat
ULTRA FLATTINTABLE



high opacity
CeilingFlat
ULTRA FLATTINTABLE

Product Summary

Use: Ceilings

Number of coats: One coat may be sufficient, however two coats may be required depending on individual situations such as application technique and depth of colour of original finish. Some tinted colours may require additional coats to achieve full opacity.

Application: Brush, roller or spray

Touch Dry: 20 minutes
(In temperatures of approx. 25°C)

Recoat: 2 Hours
(In temperatures of approx. 25°C)

Do not apply if temperature is likely to fall below 10°C during application or drying or if relative humidity is likely to exceed 80%.

Coverage: Up to 16 sq metres per litre.

Clean up: Water

Australis Ceiling Flat is a premium water based paint for use on ceilings. Australis Ceiling Flat's advanced formulation minimises roller spatter and overlap marks. With Australis Ceiling Flat's excellent opacity, one rolled coat will normally produce a satisfactory result on a white ceiling in average condition, but for best results two coats are recommended.

Surface Preparation

Previously Painted

- Remove loose and flaking paint.
- Wash to remove all grease, dirt and smoke deposits and rinse with clean water.
- Treat area to destroy mould and rinse with clean water.

- Repair cracks and defects with a good quality filler.
- Sand smooth and dust off.

- Glossy surfaces should be sanded to remove the gloss. Apply one coat of Australis Sealer Undercoat.

- Uneven or patchy surfaces require a coat of Australis Sealer Undercoat.

Unpainted paperfaced wallboard

- Dust down surfaces and apply two coats of Australis Ceiling Flat.

Unpainted Fibro Cement

- Wash to remove dirt and grease, allow to dry and apply two coats of Australis Ceiling Flat.

Unpainted Bareset Plaster or Fibrous Plaster

- Dust down surfaces, repair cracks or defects with good quality filler, sand smooth and dust off. Apply one coat of Colourtrend Binder Sealer. Apply two coats of Australis Ceiling Flat.

Application

- Stir well prior to use and occasionally during use. Apply two coats of Australis Ceiling Flat ensuring that the first coat is completely dry prior to the application of second coat.
- Thinning is not required, however in hot conditions, application will be assisted by the addition of up to 50ml of water per litre.

Safety

Keep out of reach of children. Avoid contact with skin and eyes. Avoid inhalation of vapour by providing adequate ventilation.

First Aid

Eyes: Rinse with running water for at least 15 minutes. If irritation continues seek medical advice.

Swallowed: Drink plenty of water and immediately seek medical assistance.

Inhaled: Exit area contaminated by vapours, seek medical assistance if effects continue.

Disposal

- When cleaning up after painting, ensure that paint does not get into gutters or drains as it may contaminate waterways. For a free brochure on cleaning up after painting and the disposal of surplus paint, ring 1800-807-568 (free call).
- Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.



This product complies with all the requirements of APAS specifications.
APAS APPROVAL 0260/5

"The Trade Practices Act & similar State & Territory laws. Any limitation herein on any remedy available to a consumer shall not be to the exclusion of any warranty which cannot under statute be excluded & to the extent of any conflict with such statute such warranty shall be severable."

"The Trade Practices Act & similar State & Territory laws. Any limitation herein on any remedy available to a consumer shall not be to the exclusion of any warranty which cannot under statute be excluded & to the extent of any conflict with such statute such warranty shall be severable."



Australis®



Colourtrend Paints
(Aust) Pty Ltd
ABN 50 057 442 323
481 Victoria Street
Wetherill Park NSW 2164
Tel (02) 9756 2400
Fax (02) 9756 2405
815-10104



Australis®



Australis®

Colourtrend Paints
(Aust) Pty Ltd
ABN 50 057 442 323
481 Victoria Street
Wetherill Park NSW 2164
Tel (02) 9756 2400
Fax (02) 9756 2405
815-10104



high opacity CeilingFlat

ULTRA FLAT TINTABLE

Product Summary

Use: Ceilings

Number of coats: One coat may be sufficient, however two coats may be required depending on individual situations such as application technique and depth of colour of original finish. Some tinted colours may require additional coats to achieve full opacity.

Application: Brush, roller or spray

Touch Dry: 20 minutes
(In temperatures of approx. 25°C)

Recoat: 2 Hours
(In temperatures of approx. 25°C)

Do not apply if temperature is likely to fall below 10°C during application or drying or if relative humidity is likely to exceed 80%.

Coverage: Up to 16 sq metres per litre.

Clean up: Water

Australis Ceiling Flat is a premium water based paint for use on ceilings.

Australis Ceiling Flat's advanced formulation minimises roller spatter and overlap marks. With Australis Ceiling Flat's excellent opacity, one rolled coat will normally produce a satisfactory result on a white ceiling in average condition, but for best results two coats are recommended.

Surface Preparation

Previously Painted

- Remove loose and flaking paint.
- Wash to remove all grease, dirt and smoke deposits and rinse with clean water.
- Treat area to destroy mould and rinse with clean water.
- Repair cracks and defects with a good quality filler.
- Sand smooth and dust off.

• Glossy surfaces should be sanded to remove the gloss. Apply one coat of Australis Sealer Undercoat.

• Uneven or patchy surfaces require a coat of Australis Sealer Undercoat.

Unpainted paper-faced wallboard

• Dust down surfaces and apply two coats of Australis Ceiling Flat.

Unpainted Bare-set Plaster or Fibrous Plaster

- Dust down surfaces, repair cracks or defects with good quality filler, sand smooth and dust off. Apply one coat of Colourtrend Binder Sealer. Apply two coats of Australis Ceiling Flat.

Application

- Stir well prior to use and occasionally during use. Apply two coats of Australis Ceiling Flat ensuring that the first coat is completely dry prior to the application of second coat.
- Thinning is not required, however in hot conditions, application will be assisted by the addition of up to 50ml of water per litre.

Safety

Keep out of reach of children. Avoid contact with skin and eyes. Avoid inhalation of vapour by providing adequate ventilation.

First Aid

Eyes: Rinse with running water for at least 15 minutes. If irritation continues seek medical advice.

Swallowed: Drink plenty of water and immediately seek medical assistance.

Inhaled: Exit area contaminated by vapours, seek medical assistance if effects continue.

Disposal

- When cleaning up after painting, ensure that paint does not get into gutters or drains as it may contaminate waterways. For a free brochure on cleaning up after painting and the disposal of surplus paint, ring 1800-807-568 (free call).
- Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.



This product complies with all the requirements of APAS specifications.
APAS APPROVAL 0260/5

The benefits conferred by this guarantee are in addition to all other rights & remedies in respect of the product which the consumer has under the Trade Practices Act & similar State & Territory laws. Any limitation based on any remedy available to a consumer shall not be of the nature of any warranty which cannot under statute be excluded & to the extent of any conflict with such statute such warranty shall be severable.

The benefits conferred by this guarantee are in addition to all other rights & remedies in respect of the product which the consumer has under the Trade Practices Act & similar State & Territory laws. Any limitation based on any remedy available to a consumer shall not be of the nature of any warranty which cannot under statute be excluded & to the extent of any conflict with such statute such warranty shall be severable.



Australis®

AUSTRALIS CeilingFlat IS A
PREMIUM INTERIOR ULTRA FLAT
CEILING PAINT FORMULATED TO
PRODUCE A SUPERIOR FINISH.

•12 YEAR•
GUARANTEED
NOT TO CRACK PEEL OR BLISTER*
*SEE CONDITIONS ELSEWHERE ON LABEL



high opacity
CeilingFlat
ULTRA FLAT TINTABLE

9 322553 013650
815-100 15 Litre WHITE

Colourtrend Paints
(Aust) Pty Ltd
ABN 50 057 442 323
481 Victoria Street
Wetherill Park NSW 2164
Tel (02) 9756 2400
Fax (02) 9756 2405
815-10104



AUSTRALIS CeilingFlat IS A
PREMIUM INTERIOR ULTRA FLAT
CEILING PAINT FORMULATED TO
PRODUCE A SUPERIOR FINISH.

•12 YEAR•
GUARANTEED
NOT TO CRACK PEEL OR BLISTER*
*SEE CONDITIONS ELSEWHERE ON LABEL



high opacity
CeilingFlat
ULTRA FLAT TINTABLE

9 322553 013650
815-100 15 Litre WHITE

Colourtrend Paints
(Aust) Pty Ltd
ABN 50 057 442 323
481 Victoria Street
Wetherill Park NSW 2164
Tel (02) 9756 2400
Fax (02) 9756 2405
815-10104



high opacity
CeilingFlat
ULTRA FLAT TINTABLE

Product Summary

Use: Ceilings

Number of coats: One coat may be sufficient, however two coats may be required depending on individual situations such as application technique and depth of colour of original finish. Some tinted colours may require additional coats to achieve full opacity.

Application: Brush, roller or spray

Touch Dry: 20 minutes

(In temperatures of approx. 25°C)

Recat: 2 Hours

Do not apply if temperature is likely to fall below 10°C during application or drying or if relative humidity is likely to exceed 80%.

Coverage: Up to 16 sq metres per litre.

Clean up: Water

Australis Ceiling Flat is a premium water based paint for use on ceilings.

Australis Ceiling Flat's advanced formulation minimises roller spatter and overlap marks. With Australis Ceiling Flat's excellent opacity, one rolled coat will normally produce a satisfactory result on a white ceiling in average condition, but for best results two coats are recommended.

Surface Preparation

Previously Painted

- Remove loose and flaking paint.
- Wash to remove all grease, dirt and smoke deposits and rinse with clean water.
- Treat area to destroy mould and rinse with clean water.
- Repair cracks and defects with a good quality filler.
- Sand smooth and dust off.

Glossy surfaces should be sanded to remove the gloss. Apply one coat of Australis Sealer Undercoat.

- Uneven or patchy surfaces require a coat of Australis Sealer Undercoat.
- Dust down surfaces and apply two coats of Australis Ceiling Flat.

Unpainted paperfaced wallboard

- Dust down surfaces and apply two coats of Australis Ceiling Flat.
- Wash to remove dirt and grease, allow to dry and apply two coats of Australis Ceiling Flat.

Unpainted Bareset Plaster or Fibrous Plaster

- Dust down surfaces, repair cracks or defects with good quality filler, sand smooth and dust off. Apply one coat of Colourtrend Binder Sealer. Apply two coats of Australis Ceiling Flat.

Application

- Stir well prior to use and occasionally during use. Apply two coats of Australis Ceiling Flat ensuring that the first coat is completely dry prior to the application of second coat.
- Thinning is not required, however in hot conditions, application will be assisted by the addition of up to 50ml of water per litre.

Safety

Keep out of reach of children. Avoid contact with skin and eyes. Avoid inhalation of vapour by providing adequate ventilation.

First Aid

Eyes: Rinse with running water for at least 15 minutes. If irritation continues seek medical advice.

Swallowed:

Drink plenty of water and immediately seek medical assistance.

Inhaled:

Exit area contaminated by vapours, seek medical assistance if effects continue.

Disposal

- When cleaning up after painting, ensure that paint does not get into gutters or drains as it may contaminate waterways. For a free brochure on cleaning up after painting and the disposal of surplus paint, ring 1800-807-568 (free call).
- Do not reuse empty cans. This can is recyclable. Check with your local council to see if it is participating in a steel can recycling programme.



AUSTRALIAN PAINT APPROVAL SCHEME

This product complies with all the requirements of APAS specifications. APAS APPROVAL 0260/5

"The benefits conferred by this guarantee are in addition to all other rights & remedies in respect of the product which the consumer has under the Trade Practices Act & similar State & Territory laws. Any limitation herein on any remedy available to a consumer shall not be to the exclusion of any warranty which cannot under statute be excluded & to the extent of any conflict with such statute such warranty shall be severable."

"The benefits conferred by this guarantee are in addition to all other rights & remedies in respect of the product which the consumer has under the Trade Practices Act & similar State & Territory laws. Any limitation herein on any remedy available to a consumer shall not be to the exclusion of any warranty which cannot under statute be excluded & to the extent of any conflict with such statute such warranty shall be severable."