

# Australis®

AUSTRALIS SuperTrim® IS AN INNOVATIVE PURE ACRYLIC ENAMEL, DEVELOPED TO PROVIDE A DURABLE HIGH GLOSS, NON YELLOWING INTERIOR-EXTERIOR FINISH. AUSTRALIS SuperTrim® IS EXCELLENT FOR USE ON DOORS, WALLS, WINDOWS AND TRIM.

**12 YEAR**  
**GUARANTEED**  
NOT TO CRACK, PEEL OR BLISTER\*  
\*THE CONDITIONS REFERRED TO ON LABEL

interior - exterior

# SuperTrim®

ULTRA PREMIUM GLOSS ACRYLIC ENAMEL

GLOSS

INT / EXT | GLOSS



9 322553 015937

171-100 1 Litre WHITE



## interior - exterior SuperTrim®

ULTRA PREMIUM GLOSS ACRYLIC ENAMEL

Australis SuperTrim may be used throughout the home on doors, walls, windows and trim in areas including kitchens, bathrooms and laundries. Australis SuperTrim is extremely low odour.

### Product Summary

|  |                                  |
|--|----------------------------------|
| Use:   | Interior - Exterior              |
| Application:                                       | Brush, short nap roller or spray |
| Drying Time on a day of around 25°C                |                                  |
| Avoid painting in hot conditions                   |                                  |
| Touch Dry:   | 30 minutes                       |
| Drying time will be extended by lower temperatures |                                  |
| Recoat:  | 2 hours at 25°C                  |
| Recoat:  | 3 hours at 20°C                  |
| Clean Up:  | Water                            |
| Coverage:  | Up to 16 sq metres per litre     |

### Directions

#### Prepared Surfaces

- Ensure surface to be painted is sound (see soundness).
- Remove all traces of dirt, grease, oil and any other contaminant.
- Remove all flaking, peeling material.
- Fill all imperfections with appropriate filler, spot prime repaired areas.
- Dust down and apply one coat of Australis PerfectPrep®, followed by two coats of Australis SuperTrim, sanding lightly between coats.

#### Timber New

- Sand to remove all greying timber.
- Fill imperfections with appropriate filler and sand all dressed timber. Dust down and apply one coat of Australis PerfectPrep when dry, apply two coats of Australis SuperTrim, sanding lightly between coats.

#### MDF New

- Sand lightly, dust down and apply one coat of Australis PerfectPrep, when dry apply two coats of Australis SuperTrim, sanding lightly between coats.

#### Brick, Masonry, Fibre Cement New

- Ensure surface to be painted is free from mould, dirt, dust or any other contaminant. Fill imperfections with appropriate filler, sand down. Dust off and apply one coat of Australis PerfectPrep, when dry apply two coats of Australis SuperTrim, sanding lightly between coats.

### Application

- Stir thoroughly before and during use using a broad flat paddle with a scooping motion.
- Do not apply if temperature is likely to fall below 10°C during application or drying period or should relative humidity exceed 80%.
- Apply two coats of Australis SuperTrim to a properly prepared surface, sanding lightly between coats.
- \*Perfect Prep will not achieve optimal adhesion for seven days.

### Soundness

- To determine the soundness of the surface to be painted, cut a small x with a sharp blade in the coating, firmly apply cello tape and sharply remove. Any evidence of the paint film adhering to the tape is indicative of an unsound surface. This process should be carried out at several locations to test the entire surface.

### Safety

Keep out of the reach of children. Avoid contact with skin or eyes. Avoid inhalation of vapour by providing adequate ventilation.

#### First aid

**Eyes:** rinse with running water for at least 15 minutes. If irritation persists seek medical assistance.

**Swallowed:** Drink plenty of water and immediately seek medical assistance.

**Inhaled:** Exit area contaminated by vapours, seek medical assistance if effects continue.

### Disposal

- When cleaning up after painting, ensure that paint does not get into gutters or drains as it may contaminate waterways. For a free brochure on cleaning up after painting and the disposal of surplus paint, ring 1800-807-568 (free call).
- Do not reuse empty can. This can is recyclable. Check with your local council to see if it is participating in steel can recycling programme.

\*The benefits conferred by this guarantee are in addition to all other rights & remedies in respect of the product which the consumer has under the Trade Practices Act & similar State & Territory laws. Any limitation herein on any remedy available to a consumer shall not be to the exclusion of any warranty which cannot under statute be excluded & to the extent of any conflict with such statute such warranty shall nevertheless apply.



Colourtrend Paints  
(Aust) Pty Ltd  
ABN 50 057 442 323  
481 Victoria Street  
Wentworth Park NSW 2164  
Tel (02) 9756 2400  
Fax (02) 9756 2405  
171-01035

